

Pilot series 200/A

The **pilot series 200/A** is a mechanical device which enables the working principle and the setpoint modifications of pilot operated gas pressure regulators. The pilot is optimized to enhance the accuracy and minimize the lock-up performances.



Reflux 819



Dixi



ASX 176



Reflux 819/FO



Reval 182



ASX 176/FO



Dixi AP



Terval R



Terval/AP

Features	Values		
Ambient temperature* (TS ¹)	from -20 °C to +60 °C from -4 °F to +140 °F		
Inlet gas temperature*	from -20 °C to +60 °C from -4 °F to +140 °F		
Inlet pressure (MAOP / p _{umax} ¹)	10.2 MPa 1479 psig (depending on the model)		
Range of downstream pressure (Wd ¹)	from 0.03 to 7.4 MPa from 4.3 to 1073 psig (depending on the model)		
Models for Reflux 819 ASX 176 Terval/AP	204/A + Prereducer (R14)	205/A + Prereducer (R14)	207/A + Prereducer (R14)
Design pressure* (PS ¹ / DP ²)	up to 10.2 MPa up to 1479 psig		
Minimum set-point P _{ds min}	0.03 MPa 4.3 psig	2 MPa 290 psig	4.1 MPa 595 psig
Maximum set-point P _{ds max}	4.3 MPa 623 psig	6 MPa 870 psig	7.4 MPa 1073 psig
Models for Reflux 819/FO ASX 176/FO	204/A FO + Prereducer (R14)	205/A FO + Prereducer (R14)	207/A FO + Prereducer (R14)
Design pressure* (PS ¹ / DP ²)	up to 10.2 MPa up to 1479 psig		
Minimum set-point P _{ds min}	0.1 MPa 14.5 psig	2 MPa 290 psig	4.1 MPa 595 psig
Maximum set-point P _{ds max}	3.3 MPa 478 psig	6 MPa 870 psig	7.4 MPa 1073 psig
Models for Reval 182 Terval R	201/A + Prereducer (R31)		204/A + Prereducer (R14)
Design pressure* (PS ¹ / DP ²)	up to 2.5 MPa up to 362 psig		
Minimum set-point P _{ds min}	0.7 kPa 0.1 psig	0.02 MPa 2.9 psig	
Maximum set-point P _{ds max}	58 kPa 8.41 psig	1.2 MPa 174 psig	

Features	Values	
Models for Dixi Dixi AP	204/A Dixi + Prereducer (R14)	204/A Dixi AP + Prereducer (R14)
Design pressure* (PS ¹ / DP ²)	up to 1.6 MPa up to 232 psig	up to 8.5 MPa up to 1232 psig
Minimum set-point P _{ds min}	0.03 MPa 4.35 psig	0.03 MPa 4.35 psig
Maximum set-point P _{ds max}	0.6 MPa 87 psig	2.5 MPa 362 psig
⁽¹⁾ according to EN334 standard ⁽²⁾ according to ISO 23555-1 standard ^(*) NOTE: Different functional features and/or extended temperature ranges may be available on request. Stated inlet gas temperature range is the maximum for which the equipment's full performance, including accuracy is guaranteed. Product may have a different pressure or temperature ranges according to the version and/or installed accessories.		

Table 1 Features

Materials and Approvals

Part	Material
Body	Aluminum
Cover	Aluminum
Obturator	NBR
Seat	Stainless steel
Diaphragms	Nitrile rubber
Sealing rings	NBR
Screws	Stainless steel
NOTE: The materials indicated above refer to the standard models. Different materials can be provided according to specific needs.	

Table 2 Materials

The **Pilot 200/A** is designed according to the EN334 where applicable.
 Directive 2014/68/EU (PED) is not applicable due to Article 4 paragraph 3 of the Directive.



EN 334

Pilot series 200/A competitive advantages



Compact and simple design



High accuracy

Remote set-point variation
option (CS | FIO | MP)

Easy maintenance