

PFR600

The **PFR600** is a double stage gas pressure regulator by Pietro Fiorentini. Designed to ensure continuous gas supply while maintaining a high level of safety with reduced emission. The PFR600 is a service regulator without slam-shut device, incorporating a double token relief valve (IRV) with partial relief capacity. It is particularly suitable for low pressure natural gas distribution systems for residential users. It should be used with previously filtered non-corrosive gases including biomethane and RNG (Renewable Natural Gas). The PFR600 is Hydrogen Ready for NG-H2 blending.





Residential users

Features	Values			
Design pressure* (PS ¹ / DP ²)	up to 860 kPa up to 125 psig			
	Standard version		Arctic version	
Ambient temperature* (TS ¹)**	-30°C to +65°C -20°F to +150°F		-40°C to +65°C -40°F to +150°F	
Inlet gas temperature*,***	-20°C to +65°C -4°F to +	o +150°F -30°C to +65°(C -20°F to +150°F
Inlet pressure (MAOP / p _{umax} 1)	from 69 kPa to 0.69 MPa from 10 psig to 100 psig			
Nominal capacity	17 Sm3/h 600 scfh	28 Sm3/h 1000 scfh		40 Sm3/h 1400 scfh
Minimum inlet pressure	69 kPa 10 psig	69 kPa 10 psig		103.4 kPa 15 psig
1st cut set point	6.9 kPa 1 psig	10.3 kPa 1.5 psig		27.6 kPa 4 psig
Overpressure protection (OPP)	12.8 kPa 1.85 psig	13.8 kPa 2 psig		34.5 kPa 5 psig
Range of downstream pressure Wds	from 1.3 kPa to 13.8 kPa from 5" w.c. to 2 psig			
Accuracy	According to ANSI B109.4 and CSA 6.18			
Lock-up pressure	According to ANSI B109.4 and CSA 6.18			
Connections*	In-line / 90° configuration 3/4" or 1" NPT according to ANSI B1.20.1, other configu- rations or connections on request			

ording to EN334 standard

according to ISO 23555-1 standard

(r) NOTE: Different functional features and/or extended temperature ranges may be available on request. Stated inlet gas temperature range is the maximum for which the equipment's full performance, including accuracy is guaranteed. Product may have a different pressure or temperature ranges according to the version and/or installed accessories.

(***) NOTE: Stated temperature range is the range for which the equipment's full performance, including accuracy and lock-up are guaranteed. Some body

materials, if multiple choices are available, may not be suitable for all the available versions shown.

Table 1 Features



Materials and Approvals

Part	Material
Body	Aluminum
Cover	Aluminum
Diaphragms and seats	Nitrile rubber
Sealing rings	Nitrile

NOTE: The materials indicated above refer to the standard models. Different materials can be provided according to specific needs.

Table 2 Materials

Construction Standards and Approvals

The PFR600 regulator is designed according to ANSI B109.4 and CSA 6.18



PFR600 competitive advantages





Built-in thermal valve option



Built-in strainer



Suitable for outdoor installations

Bio 209 Hig

Biomethane (RNG) compatible and 20% Hydrogen blending compatible. Higher blending available on request

Pietro Fiorentini S.p.A.

Via E.Fermi, 8/10 | 36057 Arcugnano, Italy | +39 0444 968 511 sales@fiorentini.com

Pietro Fiorentini USA Inc 606 Park Drive | Weirton WV 26062

606 Park Drive | Weirton, WV 26062, USA | +1 304 232 9115 fio.westvirginia@fiorentini.com

